(19) Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) Publication number : **0 490 704 A2**

(12) EUROPEAN PATENT APPLICATION

(21) Application number : **91311637.2**

(22) Date of filing : **13.12.91**

(51) Int. Cl.[5] : **B32B 27/36**, B32B 27/20, C08J 5/18, C08K 3/22, C08K 3/26, C08K 3/34, C08K 5/00

(30) Priority : **13.12.90 JP 401878/90**
27.03.91 JP 63516/90

(43) Date of publication of application :
17.06.92 Bulletin 92/25

(84) Designated Contracting States :
BE DE FR GB IT NL

(71) Applicant : **TORAY INDUSTRIES, INC.**
2-1, Nihonbashi Muromachi 2-chome Chuo-ku
Tokyo 103 (JP)

(72) Inventor : **Ito, Tatsuya**
1419, Oaza Godo, Godo-cho
Anpachi-gun, Gifu 503-23 (JP)
Inventor : **Tsunashima, Kenji**
1-22, Daigo Kamihayama-cho, Fushimi-ku
Kyoto-shi, Kyoto 601-13 (JP)
Inventor : **Yamauchi, Hideyuki**
696-2, Noji-cho
Kusatsu-shi, Shiga 525 (JP)
Inventor : **Aoki, Seizo**
454, Oono, Tsuchiyama-cho
Koka-gun, Shiga 528-02 (JP)
Inventor : **Kurome, Hirokazu**
10-B3-22, Sonoyama 2-chome
Otsu-shi, Shiga 520 (JP)

(74) Representative : **Coleiro, Raymond et al**
MEWBURN ELLIS 2 Cursitor Street
London EC4A 1BQ (GB)

(54) Process for forming a polyester film.

(57) A polyester film, which is substantially non-oriented and whose main component is polyethylene terephthalate (PET), is formed as a shaped article, for example, a package, under conditions in which the film has no yield point. The ability of the polyester film to form the shaped article is improved, and a shaped article having a good uniformity in thickness can be obtained. Further, the range of temperature conditions causing no yield point can be enlarged by laminating a PET polyester which originally tends to have a yield point when by itself, onto a polyester having no yield point.

EP 0 490 704 A2

BNSDOCID: <EP_____0490704A2_I_>